



# Product Data Sheet

## ADD-2568

### GENERAL

**ADD-2568** is a standard VOC-free silicone-based foam control additive for aqueous emulsion paints and adhesives. It can prevent foam and bubble formation during paint production, filling and application.

### SPECIFICATIONS

Composition	: Solution of foam-destroying polysiloxanes and hydrophobic solids
Specific gravity @ 20°C	: ca. 1.02 g/cm <sup>3</sup>
Appearance	: Clear liquid

### APPLICATIONS AND USAGE

**ADD-2568** is a standard VOC-free silicone-based foam control additive that is easy to incorporate in all kinds of aqueous emulsion systems.

**ADD-2568** is recommended for defoaming all common aqueous paint and adhesive systems. It is also suited for high gloss emulsion systems based on acrylate/PU or PU in the PVC range of 0 to 25.

**ADD-2568** can be added at any stage during production. The amount of defoamer used is often divided into 2 parts (We recommend adding 2/3 into the millbase and 1/3 into the letdown).

**ADD-2568** can be added prior to processing. If added to the finished product, care should be taken to ensure uniform distribution.

**0.1-1.0%** on total formulation weight

### STORAGE, SAFETY & HANDLING

**ADD-2568** should be stored in a cool dry place. When kept in an original unopened container, it will keep up to 5 years from the date of manufacture. **ADD-2568** should be handled in accordance with good industrial practice. Detailed information can be found in the Safety Data Sheet.