

Section 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product name: ADD-4010

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Additive for coating industries

1.3. Details of the supplier of the safety data sheet

Company name: ADD Additives BV

Daltonstraat 42

3846 BX Harderwijk

The Netherlands

Email: info@add-additives.com

1.4. Emergency telephone numberEmergency tel: +31-880701700 (9:00 -17:00)
(office hours only)**Section 2: Hazards identification****2.1. Classification of the substance or mixture**Classification under CLP: * Asp. Tox. 1: H304; STOT SE 3: H336; Aquatic Chronic 3: H412; Flam. Liq. 3: H226;
STOT SE 3: H335**Most important adverse effects:** Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.**2.2. Label elements****Label elements:****Hazard statements:** * H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

GHS08: Health hazard



SAFETY DATA SHEET

ADD-4010

Page: 2

Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/... equipment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water .

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

* Hazardous ingredients:

SOLVESSO-100 - REACH registered number(s): 01-2119455851-35

EINECS	CAS	PBT / WEL	CLP Classification	Percent
918-668-5	64742-95-6	-	Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H335; Aquatic Chronic 2: H411; STOT SE 3: H336	1-25%

N-BUTYL ACETATE - REACH registered number(s): 01-2119485493-29-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	1-25%

2-METHOXY-1-METHYLETHYL ACETATE - REACH registered number(s): 01-2119475791-29-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-603-9	108-65-6	Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226	1-25%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

[cont...]

SAFETY DATA SHEET

ADD-4010

Page: 3

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

[cont...]

SAFETY DATA SHEET

ADD-4010

Page: 4

Suitable packaging: Not applicable.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

N-BUTYL ACETATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	724 mg/m ³	966 mg/m ³	-	-

DNEL/PNEC Values

Hazardous ingredients:

SOLVESSO-100

Type	Exposure	Value	Population	Effect
DNEL	Dermal	25	Workers	Systemic
DNEL	Inhalation	150	Workers	Systemic
DNEL	Oral	11	Consumers	Systemic
DNEL	Dermal	11	Consumers	Systemic
DNEL	Inhalation	32	Consumers	Systemic

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Not miscible

[cont...]

SAFETY DATA SHEET

ADD-4010

Page: 5

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Boiling point/range°C: >35

Flammability limits %: lower: N/A

Flash point°C: 24

Autoflammability°C: N/A

Relative density: 0.983

VOC g/l: 472

Melting point/range°C: N/A

upper: N/A

Part.coeff. n-octanol/water: No data available.

Vapour pressure: 10.7 hPa

pH: N/A

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

SOLVESSO-100

DERMAL	RBT	LD50	>3160	mg/kg
ORAL	RAT	LD50	3592	mg/kg

[cont...]

SAFETY DATA SHEET

ADD-4010

Page: 6

N-BUTYL ACETATE

ORL	RAT	LD50	10768	mg/kg
-----	-----	------	-------	-------

2-METHOXY-1-METHYLETHYL ACETATE

IPR	MUS	LD50	750	mg/kg
ORL	RAT	LD50	8532	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
STOT-single exposure	INH	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

SOLVESSO-100

Daphnia magna	48H EC50	3.2	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H ErC50	2.9	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	9.2	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

[cont...]

SAFETY DATA SHEET

ADD-4010

Page: 7

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Recovery operations: Not applicable.

Waste code number: 08 01 11

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1866

14.2. UN proper shipping name

Shipping name: * RESIN SOLUTION
(SOLVESSO-100; N-BUTYL ACETATE; 2-METHOXY-1-METHYLETHYL ACETATE)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

[cont...]

SAFETY DATA SHEET

ADD-4010

Page: 8

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EC) No 1272/2008.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

